

# Window Product Selection Guide



Products are available with a full range of glass, screen, limit lock and muntin choices. Most products can be curved to meet field conditions. In addition, most aluminum surfaces can be coated with the full range of aluminum finishes including paint conforming to AAMA 2604 and AAMA 2605 or anodize conforming to AAMA 611.

	MODEL	FRAME DEPTH	AAMA/NDMA/CSA 101/ LS2/A-440-11 DESIGNATION	AAMA/NDMA/CSA 101/ LS2/A-440-17 DESIGNATION	TEST SIZE PER AAMA/NDMA/CSA 101/LS2/A-440	CSA A440 DESIGNATION	AIR INFILTRATION PER AAMA/NDMA/CSA 101/LS2/A-440	WATER RESISTANCE (PSF) PER ASTM E 331	UNIFORM LOAD DEFLECTION PER ASTM E330 (PSF)	UNIFORM LOAD STRUCTURAL PER ASTM E330 (PSF)	FORCED ENTRY RESISTANCE (TYPE/GRADE)	U-FACTOR PER NFRC 100	CONDENSATION RESISTANCE (CR) PER NFRC 500	CRF - FRAME PER AAMA 1503	MATCHING FIXED FRAME
<div><div><div></div><div></div></div><div><div></div><div></div></div></div> <div>hung</div>															
SINGLE HUNG, SIDE LOAD	TR-9100	3-1/4"	H-AW50	AW-PG50-H	60" x 99"		0.3 @ 6.2 PSF	15	50	75	T:A/G:10	0.45*		56	TR-7100
SINGLE HUNG, SIDE LOAD	TR-9700	3-1/4"	H-AW40	AW-PG40-H	60" x 99"		0.3 @ 6.2 PSF	15	40	60	T:A/G:10	0.50*			TR-7100
SINGLE HUNG, SIDE LOAD	8400TL	4"	H-AW70	AW-PG70-H	60" x 99"		0.3 @ 6.2 PSF	15	70	105	T:A/G:10	0.51	32	55	8400TL
SINGLE HUNG, SIDE LOAD	AA®5450	4-5/8"		AW-PG65-H	60" x 99"	A3/B4/C3	0.3 @ 6.2 PSF	15	50	75	T:A/G:10	0.24	59	75	AA®5450
DOUBLE HUNG, SIDE LOAD	8400TL	4"	H-AW70		60" x 99"		0.3 @ 6.2 PSF	15	70	105	T:A/G:11	0.53	33	51	8400TL
DOUBLE HUNG, SIDE LOAD	AA®5450	4-5/8"		AW-PG65-H	60" x 99"	A3/B4/C3	0.3 @ 6.2 PSF	15	50	75	T:A/G:10	0.26	59	71	AA®5450
<div><div><div></div><div></div></div><div><div></div><div></div></div></div> <div>sliding</div>															
SINGLE SLIDE	8400TL	4"	HS-AW70		99" x 79"		0.3 @ 6.2 PSF	15	70	105	T:A/G:10	0.56	30	50	8400TL
SINGLE SLIDE	AA®5450	4-5/8"		AW-PG40-HS	99" x 79"	A2/B4/C3	0.3 @ 6.2 PSF	10	40	60	T:A/G:10	0.25		76	AA®5450
DOUBLE SLIDE	8400TL	4"	HS-AW70		99" x 79"		0.3 @ 6.2 PSF	15	70	105	T:A/G:10				8400TL
DOUBLE SLIDE	AA®5450	4-5/8"		AW-PG50-HS	99" x 79"	A2/B4/C3	0.3 @ 6.2 PSF	10	45	67.5	T:A/G:10	0.27		69	AA®5450

This guide was developed to assist the specifier in choosing the right product for your project based on design pressure and overall performance to ensure a successful and enduring application. For Hurricane Resistant or Blast Resistant options refer to the Hurricane Resistant Window Product Selection Guide and Blast Mitigation Window Product Selection Guide.



\*Products simulated to NFRC 100 sizes using Win-Therm software.

	MODEL	FRAME DEPTH	AMMADMA CSA 101 LS 2/A-440-11 DESIGNATION	AMMADMA CSA 101 LS 2/A-440-11 DESIGNATION	TEST SIZE PER AMMADMA CSA 101/LS 2/A-440	CSA 440 DESIGNATION	AIR INFILTRATION PER AMMADMA CSA 101/LS 2/A-440	WATER RESISTANCE (PSF) PER ASTM E 331	UNIFORM LOAD DEFLECTION PER ASTM E 330 (PSF)	UNIFORM LOAD STRUCTURAL PER ASTM E 330 (PSF)	FORCED ENTRY RESISTANCE (TYPE GRADE)	U-FACTOR PER NFRC 100	CONDENSATION RESISTANCE (CR) PER NFRC 300	CRF - FRAME PER AMMA 1503	MATCHING FIXED FRAME
	casement														
OVERLAP INSWING	8225TL	2-1/4"	C-AW90	AW-PG90-C	36" x 60"		0.1 @ 6.2 PSF	15	90	135	T:B/G:10	0.46	40		8225TL
OVERLAP OUTSWING	8225TL	2-1/4"	C-AW90	AW-PG90-C	36" x 60"		0.1 @ 6.2 PSF	15	90	135	T:B/G:10	0.47	39		8225TL
OVERLAP INSWING	526	2-1/4"													516/518
OVERLAP OUTSWING	526	2-1/4"				A3/B5/C5	0.1 @ 6.2 PSF	10			T:B/G:10				516/518
OVERLAP INSWING	AA®4325	3-1/4"	C-AW80	AW-PG80-C	36" x 60"	A3/B7/C5	0.1 @ 6.2 PSF	15	80	135	T:B/G:10				AA®4325
OVERLAP OUTSWING	AA®4325	3-1/4"	C-AW80	AW-PG80-C	36" x 60"	A3/B7/C5	0.1 @ 6.2 PSF	15	80	135	T:B/G:10				AA®4325
OVERLAP INSWING	AA®4325	3-1/4"	C-AW50	AW-PG50-C	36" x 60"	A3/B7/C5	0.1 @ 6.2 PSF	15	80	135	T:B/G:10				Savio (ADA)
OVERLAP INSWING	NX-3200	3-1/4"	C-AW80	AW-PG80-C	36" x 60"		0.1 @ 6.2 PSF	15	80	120	T:B/G:10	0.42	43		NX-3800
OVERLAP OUTSWING	NX-3100	3-1/4"	C-AW80	AW-PG80-C	36" x 60"		0.1 @ 6.2 PSF	15	80	120	T:B/G:10	0.42	43	55	NX-3800
OVERLAP OUTSWING	NX-310	3-1/4"	C-AW90	AW-PG90-C	36" x 60"	A3/B7/C5	0.1 @ 6.2 PSF	15	90	135	T:B/G:10	0.47	48	66	NX-380
FRAMELESS OUTSWING	GLASSvent® WINDOWS	2-1/8"/2-3/4"						12	40/70	60/105	T:B/G:10	0.56		51	Storefront
FRAMELESS OUTSWING	GLASSvent® WINDOWS	2-11/16"/3-7/16"	C-AW90	AW-PG90-C	36" x 60"	A3/B7/C5	0.1 @ 6.2 PSF	15	90	135	T:B/G:10				Curtainwall
FRAMELESS OUTSWING	GLASSvent®UT WINDOWS	3-1/8"/3-7/8"	C-CW40	CW-PG40-C	32" x 60"	A3/B7/C3	0.1 @ 6.2 PSF	12/15	40	60	T:B/G:10			80	2-Cam Handles
FRAMELESS OUTSWING	GLASSvent®UT WINDOWS	3-1/8"/3-7/8"	C-CW70	CW-PG70-C	32" x 60"	A3/B7/C5	0.1 @ 6.2 PSF	12/15	70	105	T:B/G:10			80	3-Cam Handles
FRAMELESS OUTSWING	GLASSvent®UT WINDOWS	4-3/8"/5-1/8"	C-CW80	CW-PG80-C	36" x 60"	A3/B7/C5	0.1 @ 6.2 PSF	12/15	70	105	T:B/G:10			80	Roto / Lock
FRAMELESS OUTSWING	GLASSvent®UT WINDOWS	4-3/8"/5-1/8"	C-AW90	AW-PG90-C	36" x 60"	A3/B7/C5	0.1 @ 6.2 PSF	15	90	135	T:B/G:10			80	3-Cam Handles
	projected														
OVERLAP PROJECT IN	8225TL	2-1/4"	AP-AW90	AW-PG90-AP	60" x 36"		0.1 @ 6.2 PSF	15	90	135	T:B/G:10	0.46	41	55	8225TL
OVERLAP PROJECT OUT	8225TL	2-1/4"	AP-AW90	AW-PG90-AP	60" x 36"		0.1 @ 6.2 PSF	15	90	135	T:B/G:10	0.48	39	58	8225TL
OVERLAP PROJECT IN	526	2-1/4"				A3/B5/C5									516/518
OVERLAP PROJECT OUT	526	2-1/4"				A3/B5/C5									516/518
OVERLAP PROJECT IN	AA®4325	3-1/4"	AP-AW80	AW-PG80-AP	60" x 36"	A3/B7/C5	0.1 @ 6.2 PSF	15	80	120	T:B/G:10	0.22	74	76	AA®4325
OVERLAP PROJECT OUT	AA®4325	3-1/4"	AP-AW80	AW-PG80-AP	60" x 36"	A3/B7/C5	0.1 @ 6.2 PSF	15	80	120	T:B/G:10	0.23	68		AA®4325
OVERLAP PROJECT IN	NX-3400	3-1/4"	AP-AW80	AW-PG80-AP	60" x 36"		0.1 @ 6.2 PSF	15	80	120	T:B/G:10	0.41	43		NX-3800
OVERLAP PROJECT OUT	NX-3500	3-1/4"	AP-AW80	AW-PG80-AP	60" x 36"		0.1 @ 6.2 PSF	15	80	120	T:B/G:10	0.42	43		NX-3800
OVERLAP PROJECT OUT	NX-350	3-1/4"	AP-AW90	AW-PG90-AP	60" X 36"	A3/B7/C5	0.1 @ 6.2 PSF	15	90	135	T:B/G:10	0.47	48	66	NX-380
FRAMELESS PROJECT OUT	GLASSvent® WINDOWS	2-1/8"/2-3/4"						12	40/70	60/105	T:B/G:10	0.56		51	Storefront
FRAMELESS PROJECT OUT	GLASSvent® WINDOWS	2-11/16"/3-7/16"	AP-AW90	AW-PG90-AP	60" x 30"	A3/B7/C5	0.1 @ 6.2 PSF	15	90	135	T:B/G:10	0.76	33	51	Curtainwall
FRAMELESS PROJECT OUT	GLASSvent®UT WINDOWS	3-1/8"/3-7/8"	AP-CW40	CW-PG40-AP	48" x 32"	A3/B7/C3	0.1 @ 6.2 PSF	12/15	40	60	T:B/G:10			73	2-Cam Handles
FRAMELESS PROJECT OUT	GLASSvent®UT WINDOWS	3-1/8"/3-7/8"	AP-CW60	CW-PG60-AP	48" x 32"	A3/B7/C4	0.1 @ 6.2 PSF	12/15	60	90	T:B/G:10			73	3-Cam Handles
FRAMELESS PROJECT OUT	GLASSvent®UT WINDOWS	3-1/8"/3-7/8"	AP-CW70	CW-PG70-AP	48" x 32"	A3/B7/C5	0.1 @ 6.2 PSF	12/15	70	105	T:B/G:10			73	Roto / Lock
FRAMELESS PROJECT OUT	GLASSvent®UT WINDOWS	4-3/8"/5-1/8"	AP-AW80	CW-PG80-AP	48" x 32"	A3/B7/C5	0.1 @ 6.2 PSF	12/15	80	120	T:B/G:10			73	Roto / Lock
FRAMELESS PROJECT OUT	GLASSvent®UT WINDOWS	4-3/8"/5-1/8"	AP-AW90	AW-PG90-AP	60" x 36"	A3/B7/C5	0.1 @ 6.2 PSF	15	90	135	T:B/G:10			73	3-Cam Handles
FRAMELESS PROJECT OUT	GLASSvent®UT WINDOWS	4-3/8"	AP-AW50	AW-PG50-AP	60" X 36"	A3/B7/C5	0.1 @ 6.2 PSF	15	50	75	T:B/G:10			73	Omni Drive (ADA)

horizontal  
ventilator