

Declare.

250T/350T/500T Insulpour™ Thermal Entrances Kawneer Company, Inc.

Final Assembly: Multiple Locations in North America

Life Expectancy: 40+ Year(s)

End of Life Options: Recyclable (85-95%), Landfill (5-15%)

Ingredients:

Frame: Anodized Aluminum; **Thermal & Weathering:**

Bicyclo[2.2.1]hept-2-ene, 5-ethylidene-, polymer with ethene and 1-propene; Carbon black; Polypropylene; Talc; White mineral oil (petroleum); 1-Propene, polymer with ethene; Polymethylene polyphenyl isocyanate; 4,4'-Methylenediphenyl diisocyanate; Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1); 1,3-Isobenzofurandione, polymer with 2,2'-oxybis[ethanol]; Calcium carbonate; Calcium Oxide; Carbonic dichloride, polymer with 4,4'-(1-methylethylidene)bis[phenol]; Clay; Dicumyl-peroxide; Diethylene Glycol; Poly[oxy(methyl-1,2-ethanediyl)], α,α',α'' - 1,2,3-propanetriyltris[ω -hydroxy-; Polyethylene; Propanol, oxybis-; Zinc oxide; Ethylene glycol; **Hardware:** Stainless Steel; Iron; Zinc; Chromium, metallic; Manganese; Nickel (Metallic); Copper; Silicon; Molybdenum; Cellulose, ethyl ether

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: Not Applicable
- Declared

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

KAW-0025
EXP. 01 JAN 2025
Original Issue Date: 2018

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY
INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare