

GLASSvent™ Windows for Storefront Framing and Curtain Wall and GLASSvent™ UT Windows Kawneer Company, Inc.

Final Assembly: Multiple locations in North America

Life Expectancy: 40+ Year(s)

End of Life Options: Recyclable (75-80%), Landfill (20-25%)

Ingredients:

Frame: Anodized Aluminum; Glass: Glass, oxide, chemicals; Anodized Aluminum; Silicone Rubber; Zeolites other than erionite (clinoptilolite, phillipsite,mordenite, non-fibrous Japanese zeolite, synthetic zeolites); Amorphous silica; Siloxanes and Silicones, di-Me; Polyvinylbutyral; Calcium carbonate; Thermal & Weathering: Bicyclo[2.2.1]hept-2-ene, 5-ethylidene-, polymer with ethene and 1-propene; Polypropylene; White mineral oil (petroleum); 2-Propenoic acid, butyl ester, polymer with ethenylbenzene and 2-propenenitrile; Acrylic; Acrylonitrile-Butadiene-Styrene Copolymer; Polyurethane foams; Carbon black; Clay; Fasteners: Stainless Steel; Hardware: Copper; Zinc; Manganese; Nickel (Metallic); Tin, Organic

Living Building Challenge Criteria: Compliant

I-13 Red List:

■ LBC Red List Free

☐ LBC Red List Approved

% Disclosed: 100% at 100ppm VOC Content: Not Applicable

□ Declared

I-10 Interior Performance: Not Applicable I-14 Responsible Sourcing: Not Applicable

KAW-0010 EXP. 01 JAN 2025 Original Issue Date: 2017

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare