

## ENVIRONMENTAL PRODUCT DECLARATION

# OVERHEAD GLAZING

ALUMINUM SLOPED CURTAIN WALL



Low-cost, high-performance systems suitable for sloped glazed areas or roof mounted skylights. Kawneer products are comprised of extrusions made from one of the earth's most plentiful recyclables — aluminum. Durable and lasting, the extruded products also boast aesthetically appealing design features that can help contribute to energy efficiency and long-term sustainability.



Kawneer Company, Inc., part of Arconic's global Building and Construction Systems (BCS) business, has provided the commercial construction industry with best-in-class architectural aluminum products and service for more than 100 years. Its extensive range of solutions — from curtain walls and windows, to entrances and framing systems — help build infinite possibilities for thermal performance, hurricane resistance, blast mitigation and sun control.

Kawneer's commitment to social and environmental responsibility is rooted in high performing, sustainable solutions that extend beyond energy efficiency to elements like daylighting, acoustical efficiency, recyclability, occupant security and occupant comfort. In fact, sustainability is at the heart of Kawneer's product line, which is comprised of one of the earth's most plentiful recyclables — aluminum.

Kawneer offers architects a new way to look at the building façade, placing endless design and sustainability options at their fingertips.

For more information visit [www.kawneer.com](http://www.kawneer.com)



# ENVIRONMENTAL PRODUCT DECLARATION



**Overhead Glazing**  
Aluminum Sloped Curtain Wall

According to ISO 14025, EN 15804, and ISO 21930:2017

EPD PROGRAM AND PROGRAM OPERATOR NAME, ADDRESS, LOGO, AND WEBSITE	UL Environment 333 Pfingsten Road Northbrook, IL 60611 <a href="https://www.ul.com">https://www.ul.com</a> <a href="https://spot.ul.com">https://spot.ul.com</a>
GENERAL PROGRAM INSTRUCTIONS AND VERSION NUMBER	General Program Instructions v.2.5 March 2020
MANUFACTURER NAME AND ADDRESS	Kawneer North America 555 Guthridge Ct. Technology Park/Atlanta Norcross, GA 30092
DECLARATION NUMBER	4789733794.105.1
DECLARED PRODUCT & FUNCTIONAL UNIT OR DECLARED UNIT	Overhead Glazing, Aluminum Sloped Curtain Wall, 1 m2
REFERENCE PCR AND VERSION NUMBER	Part A: Calculation Rules for the LCA and Requirements Project Report, (IBU/UL Environment, V3.2, 12.12.2018) (IBU/UL, 2018); and, Part B: Requirements on the EPD for Self supporting façade elements based on glazed curtain walls (IBU, V1.7, 04.01.2019) (IBU, 2019)
DESCRIPTION OF PRODUCT APPLICATION/USE	Self-supporting façade element
MARKETS OF APPLICABILITY	North America
DATE OF ISSUE	October 1, 2021
PERIOD OF VALIDITY	5 Years
EPD TYPE	Company specific
EPD SCOPE	Cradle to gate
YEAR(S) OF REPORTED PRIMARY DATA	2019
LCA SOFTWARE & VERSION NUMBER	GaBi v10 (Sphera, 2020)
LCI DATABASE(S) & VERSION NUMBER	GaBi 2021 (CUP 2021.1)
LCIA METHODOLOGY & VERSION NUMBER	IPCC AR5 (GWP), CML-IA v4.8, TRACI 2.1 (Bare, 2012)
The sub-category PCR review was conducted by:	Institut Bauen und Umwelt e.V. The Independent Expert Committee (SRV) <a href="mailto:info@ibu-epd.com">info@ibu-epd.com</a>
This declaration was independently verified in accordance with ISO 14025: 2006. The UL Environment “Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report,” v3.2 (December 2018), in conformance with ISO 21930:2017, serves as the core PCR, with additional considerations from the USGBC/UL Environment Part A Enhancement (2017) <input type="checkbox"/> INTERNAL <input checked="" type="checkbox"/> EXTERNAL	 James Mellentine, Thrive ESG
This life cycle assessment was conducted in accordance with ISO 14044 and the reference PCR by:	 James Mellentine, Thrive ESG

**LIMITATIONS**

**Exclusions:** EPDs do not indicate that any environmental or social performance benchmarks are met, and there may be impacts that they do not encompass. LCAs do not typically address the site-specific environmental impacts of raw material extraction, nor are they meant to assess human health toxicity. EPDs can complement but cannot replace tools and certifications that are designed to address these impacts and/or set performance thresholds – e.g. Type 1 certifications, health assessments and declarations, environmental impact assessments, etc.

**Accuracy of Results:** EPDs regularly rely on estimations of impacts; the level of accuracy in estimation of effect differs for any particular product line and reported impact.

**Comparability:** EPDs from different programs may not be comparable. Full conformance with a PCR allows EPD comparability only when all stages of a life cycle have been considered. However, variations and deviations are possible”. Example of variations: Different LCA software and background LCI datasets may lead to differences results for upstream or downstream of the life cycle stages declared.

# ENVIRONMENTAL PRODUCT DECLARATION



Overhead Glazing  
Aluminum Sloped Curtain Wall

According to ISO 14025, EN 15804, and ISO 21930:2017

## Product Definition and Information

### Description of Company/Organization

Kawneer Company, Inc., part of Arconic's global Building and Construction Systems (BCS) business, has led the façade industry with innovative, high-performing building envelope solutions for more than a century. With locations across North America and Europe, Kawneer manufactures a broad range of architectural aluminum systems from curtain walls and entrances to framing systems and windows. Kawneer's technical expertise and product capability enhance building performance, protection and productivity to deliver inspiring buildings around the world. Part of Arconic Corporation's global Building and Construction Systems business, Kawneer innovation is advancing the frontiers of building and architectural design.

### Product Description

#### Product Identification

Kawneer curtain wall systems are designed to minimize heat gain/loss (thermal conductance) through the curtain wall systems. Once viewed as an outer skin able to keep out water and hold glass, curtain wall systems have evolved into much more, offering not only high thermal performance, but also benefits such as blast mitigation, hurricane resistance and day lighting.

Sloped glazing is defined as any glazing system or material installed on a slope more than 15 degrees with curtain wall performance in a monumental sloped system.

Overhead Glazing featuring:

- 1600 Sloped Glazing
- 2000 Skylight

The combination of aesthetics and thermal performance, curtain wall and glass manufacturers are working in concert to improve thermal efficiency. Many systems are able to integrate seamlessly with high-performing windows and doors, providing a complete façade solution that reduces energy demands and environmental impact. Thermal break technologies, as well as improved integrated sun control, are high on the list of options available in current systems.

For thermal performance, a product is considered **thermally broken** if the separation between the interior and exterior metal is 0.21 inches or greater. **Thermally improved** systems are generally defined as having a separation between the interior and exterior metal of less than 0.21 inches but not less than 1/16 inch. The sloped glazed systems have a thermally broken design using an EPDM gasket to create the spacing based on the fenestration guidelines.




Figure 1. 1600 SLOPED GLAZING



# ENVIRONMENTAL PRODUCT DECLARATION



Overhead Glazing  
Aluminum Sloped Curtain Wall

According to ISO 14025, EN 15804, and ISO 21930:2017

## Technical Specification

Table 1 Technical specification

Name	Value	Unit
Thermal transmittance (U-factor) AAMA 1503.1, AAMA 507, and NFRC 100	0.15 – 0.45	Btu/hr. ft <sup>2</sup> .°F
Solar Heat-Gain Coefficient (SHGC) NFRC 200	0.10 – 0.70	
Condensation Resistance Factor (CRF) AAMA 1503.1	33 - 82	
Water Infiltration ASTM E 331 and AAMA 501.1	10 - 20	psf
Air Infiltration ASTM E283 at 6.24 psf	0.01 – 0.06	
Impact Resistance ASTM E1886/1996, Testing Application Standard 201/202/203	Level A - E	Cfmft <sup>2</sup>

## Delivery Status

Overhead glazing is ideal for sloped glazed areas or roof mounted skylights (Kawneer, 2021).

## Industry Standards

Kawneer products are tested, certified, and labeled for the following performance standards:

- AAMA/WDMA/CSA 101/IS2/A440-17 (NAFS-North American Fenestration Standard/Specification for windows, doors, and skylights) for the most current version
- ASTM E283-04(2012), Standard Test Method for Determining Rate of Air Leakage Through Exterior Windows, Curtain Walls, and Doors Under Specified Pressure Differences Across the Specimen
- ASTM E330/E330M-14, Standard Test Method for Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference
- ASTM E331-00(2016), Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference
- ASTM E547-00(2016), Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Cyclic Static Air Pressure Difference
- ASTM E2268-04(2016), Standard Test Method for Water Penetration of Exterior Windows, Skylights, and Doors by Rapid Pulsed Air Pressure Difference
- AAMA 1503, AAMA 507 and NFRC 100 Thermal Transmittance – U-Factors
- AAMA 1503, CSA A440.2 and NFRC 500 Condensation Resistance (CRF,I,CR)



# ENVIRONMENTAL PRODUCT DECLARATION



**Overhead Glazing**  
Aluminum Sloped Curtain Wall

According to ISO 14025, EN 15804, and ISO 21930:2017

- AAMA 507 and NFRC 200 Overall Solar Heat Gain Coefficient and Visible Transmittance (SHGC) & (VT)
- AAMA 501.4-09, Recommended Static Test Method for Evaluating Curtain Wall and Storefront Systems Subjected to Seismic and Wind Induced Inter-story Drifts.
- AAMA 501.5-07, Test Method for Thermal Cycling of Exterior Walls.
- AAMA 501.1-17, Standard Test Method for Water Penetration of Windows, Curtain Walls and Doors Using Dynamic Pressure

## Base And Ancillary Materials

Overhead curtain walls are primarily made with thermally treated Aluminum extrusions and are installed offsite.

**Table 2 Base and ancillary materials**

Material	Mass (kg)	Mass (%)
Thermally treated Aluminum extrusions	7.13 – 8.54	20.42% – 23.51%
Glass	27.8	~ 78%

## Manufacturing

Kawneer’s plants produce surface-treated (anodized and painted) aluminum extrusions. After extrusion and surface treatment, thermal barriers comprised of polymers are added to the aluminum extrusions to improve thermal performance. The aluminum-polymer composite is then fabricated to the required dimensions and assembled into curtain walls with hardware.

Note that one facility, Visalia, CA, does not have extrusion capabilities and sources extruded aluminum from internal and external suppliers. Only the Springdale plant produces overhead glazing and are assembled off-site.

## Product Processing/Installation

Installation is not included in this study.

## Packaging

Kawneer products are primarily packaged using paper and plastic wrap and steel strap prior to shipping to installation sites.

## Recycling and Disposal

Product recycling is not included in this study.



# ENVIRONMENTAL PRODUCT DECLARATION



Overhead Glazing  
Aluminum Sloped Curtain Wall

According to ISO 14025, EN 15804, and ISO 21930:2017

## Environment and Health

---

**Product manufacturing:** Plant emissions to air/soil/water are monitored (if applicable) and comply with local laws.

**Product use:** Kawneer products are not expected to create exposure conditions that exceed safe thresholds for health impacts to humans or flora/fauna under normal operating conditions.

## Life Cycle Assessment Background Information

---

### Declared Unit

---

The declared unit of the underlying life cycle assessment study was one square meter (1 m<sup>2</sup>) of overhead glazing (including frame). The reference flow is 35.7 kg of product unit with framing, with a frame to glazing ration of 22% to 78% by mass. The 1.5m x 1.6m curtain wall standard size was used to derive the declared unit.

### System Boundary

---

The system boundary for the declaration is cradle-to-gate per the guiding PCR. The product life cycle stages included within this boundary are illustrated in Figure 2.



# ENVIRONMENTAL PRODUCT DECLARATION



Overhead Glazing  
Aluminum Sloped Curtain Wall

According to ISO 14025, EN 15804, and ISO 21930:2017




Figure 2. Life cycle stage diagram for cradle-to-gate production of overhead glazing

The table below represents the system boundary and scope.

Table 3 System boundary modules included and excluded from the study, in accordance with EN 15804

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED)																
PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport	Construction-installation process	Use	Maintenance	Repair	Replacement <sup>1</sup>	Refurbishment <sup>1</sup>	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND

\* X = module included, MND = module not declared



# ENVIRONMENTAL PRODUCT DECLARATION



Overhead Glazing  
Aluminum Sloped Curtain Wall

According to ISO 14025, EN 15804, and ISO 21930:2017

**Time coverage:** Kawneer primary data are to represent production within calendar year 2019. Background data for upstream and downstream processes (i.e., raw materials, energy resources, transportation, and ancillary materials) were obtained from the GaBi databases (CUP 2021.1).

**Technology coverage:** Data represent the production of aluminum extrusions at Kawneer's facilities in the United States and Canada. Primary data from Kawneer manufacturing facilities were collected and used to describe the production of aluminum extruded framing material, surface treatment, and the assembly of windows system.

As required by the PCR, over 80% of the window material by mass are represented by primary data.

**Geographical coverage:** Kawneer manufactures aluminum window products at four US facilities and one Canadian facility. As such, the geographical coverage for this study is based on North American system boundaries for all processes and products. Whenever US/Canadian background data were not readily available, European data or global data were used as proxies.

## Estimations and Assumptions

The manufacturing processes and end product are essentially the same at all manufacturing sites. Impacts and inventories for hung & sliding windows were calculated with a mass-based production-weighted average of each site's impacts and inventories.

Float glass is insulated, laminated, or tempered and added to the finished assembly. At this time, data does not include granularity to differentiate between insulate, laminated and tempered glass. As such, all glass is modeled the same.

Glass is only processed at the Cranberry facility. The remaining facilities produce and sell only the aluminum frames. For these facilities, the glass produced at the Cranberry facility was used as a proxy for the window glazing.

No significant assumptions have been made beyond the aforementioned. All of the raw materials and energy inputs have been modeled using processes and flows that closely follow actual production raw materials and processes. All of the material and energy flows have been accounted.

## Cut-off Criteria

In the case of data gaps for unit processes, the cut-off criteria as defined by ISO 21930 were applied. All available energy and material flow data have been included in the model. In cases where no matching life cycle inventories are available to represent a flow, proxy data have been applied based on conservative assumptions regarding environmental impacts.

## Data Sources

To ensure reliable results, first-hand industry data were used in combination with consistent background LCA information from the GaBi database (CUP 2021.1). The data for aluminum billet, as well as externally sourced aluminum extrusions, are based on Aluminum Association studies and are the best available. Other LCI datasets were sourced from the GaBi databases and are representative of the years 2018-2020.





# ENVIRONMENTAL PRODUCT DECLARATION



**Overhead Glazing**  
Aluminum Sloped Curtain Wall

According to ISO 14025, EN 15804, and ISO 21930:2017

## Data Quality

In order to model cradle-to-gate life cycle of traditional curtain walls, the GaBi Professional software system (v10.5) developed by Sphera, Inc. was used. All relevant background data necessary for product modeling were taken from the GaBi databases (CUP 2021.1).

Inventory data quality is judged by its precision (measured, calculated or estimated), completeness (e.g., unreported emissions), consistency (degree of uniformity of the methodology applied on a study serving as a data source) and representativeness (geographical, temporal, and technological).

To ensure reliable results, first-hand industry data were used in combination with consistent background LCA information from the GaBi databases. The data for aluminum billet, as well as externally sourced aluminum extrusions, are based on Aluminum Association studies and are the best available. Other LCI datasets were sourced from the GaBi databases.

LCI datasets from the GaBi LCI database are widely distributed and used with the GaBi Professional Software. The datasets have been used in LCA models worldwide in industrial and scientific applications in internal as well as in many critically reviewed and published studies. In the process of providing these datasets, they are cross-checked with other databases and values from industry and science.

## Allocation

No multi-output (i.e., co-product) allocation was performed in the foreground system of this study.

Allocation of background data (energy and materials) taken from the GaBi 2021 databases is documented online at <https://sphera.com/wp-content/uploads/2020/04/Modeling-Principles-GaBi-Databases-2021.pdf>.

Per the PCR guidance, recycling and recycled content in the cradle-to-gate system are modeled using the cut-off rule (a.k.a, the recycled content rule). All materials that are recycled from unit processes are considered to have left the system boundary. Recycled content is modeled in the system only when the percent of recycled content was specified in the material purchase.

## Life Cycle Assessment – Results

Results given per declared unit of product.

**Table 4. Cradle-to-gate (manufacturing, glazing and frame) LCIA results of Kawneer Overhead Glazing**

Impact Category	Unit	A1 - A3	Frame	Glazing
<b>LIFE CYCLE IMPACTS ASSESSMENT (LCIA) RESULTS</b>				
<b>IPCC, AR5 (IPCC, 2013)</b>				
Global Warming Potential	kg CO <sub>2</sub> eq	1.41E+02	5.74E+01	8.32E+01
<b>CML-IA v4.8</b>				
Abiotic Depletion (ADP elements)	kg Sb eq.	1.78E-04	5.84E-05	1.20E-04
Abiotic Depletion (ADP fossil)	MJ LHV	1.68E+03	6.77E+02	1.00E+03



# ENVIRONMENTAL PRODUCT DECLARATION



**Overhead Glazing**  
Aluminum Sloped Curtain Wall

According to ISO 14025, EN 15804, and ISO 21930:2017

Acidification Potential (AP)	kg SO <sub>2</sub> eq.	7.04E-01	3.03E-01	4.01E-01
Eutrophication Potential (EP)	kg (PO <sub>4</sub> ) <sub>3</sub> - eq.	6.42E-02	2.04E-02	4.38E-02
Ozone Layer Depletion Potential (ODP, steady state)	kg R11 eq.	2.49E-09	2.49E-09	1.90E-13
Photochemical Ozone Creation Potential (POCP)	kg C <sub>2</sub> H <sub>4</sub> eq.	-1.69E-02	2.17E-02	-3.86E-02
<b>TRACI 2.1</b>				
Acidification Potential (AP)	kg SO <sub>2</sub> eq.	7.22E-01	2.95E-01	4.27E-01
Eutrophication Potential (EP)	kg N eq.	2.94E-02	8.28E-03	2.12E-02
Ozone Layer Depletion Potential (ODP, steady state)	kg CFC 11 eq.	2.65E-09	2.65E-09	1.90E-13
Resources, Fossil fuels	MJ LHV surplus energy	1.62E+02	6.45E+01	9.71E+01
Smog Formation Potential (SFP)	kg O <sub>3</sub> eq.	8.88E+00	3.56E+00	5.32E+00
<b>RESOURCE USE INDICATORS</b>				
Renewable primary resources used as energy carrier (fuel) (RPRE)	MJ LHV	3.24E+02	2.38E+02	8.55E+01
Renewable primary resources with energy content used as material (RPRM)	MJ LHV	1.29E+00	1.29E+00	0.00E+00
Non-renewable primary resources used as an energy carrier (fuel) (NRPRE)	MJ LHV	1.90E+03	6.79E+02	1.20E+03
Non-renewable primary resources with energy content used as material (NRPRM)	MJ LHV	3.18E+00	2.23E+00	9.48E-01
Renewable secondary fuels (RSF)	MJ LHV	-	-	-
Non-renewable secondary fuels (NRSF)	MJ LHV	-	-	-
Recovered energy (RE)	MJ LHV	-	-	-
Secondary material (SM)	kg	1.38E-02	1.38E-02	0.00E+00
Use of net freshwater resources (FW)	m <sup>3</sup>	1.22E+00	1.00E+00	2.21E-01
<b>OUTPUT FLOWS &amp; WASTE FLOWS</b>				
Hazardous waste disposed (HWD)	kg	1.47E-02	1.47E-02	9.14E-08
Non-hazardous waste disposed (NHWD)	kg	3.35E+00	2.81E+00	5.40E-01
High-level radioactive waste, conditioned, to final repository (HLRW)	kg	1.03E-04	1.11E-05	9.21E-05
Intermediate and low-level radioactive waste, conditioned, to final repository (ILLRW)	kg	8.95E-02	9.01E-03	8.05E-02
Components for reuse (CRU)	kg	-	-	-
Materials for Recycling (MFR)	kg	9.70E-04	9.70E-04	0.00E+00
Materials for Energy Recovery (MER)	kg	-	-	-
Exported Electrical Energy (EEE)	kg	-	-	-
Exported Thermal Energy (EET)	kg	-	-	-

## Life Cycle Assessment – Interpretation

Results represent the cradle to gate environmental impacts of overhead glazing. Breakdown of frame and glazing impacts are shown in Figure 3 representing TRACI 2.1 (Bare, 2012) impact categories and IPCC AR5 for GWP. Glazing component is

# ENVIRONMENTAL PRODUCT DECLARATION




**Overhead Glazing**  
Aluminum Sloped Curtain Wall

According to ISO 14025, EN 15804, and ISO 21930:2017

contributing significantly to all impact categories except ODP. Float glass material and energy use during the glass processing drive the impacts for this component.


Frame impacts, on the other hand, are mostly driven by use of primary alloys – including aluminum and steel. Use of secondary aluminum in extrusion processes can reduce overall impacts significantly. Assembly, extrusion and thermal processing are the top three impactful processes mainly due to resource use during these steps.

While similar processes show variations in resource use and waste across manufacturing locations, average results are affected by production volumes rather than process variations.



**Figure 3. TRACI Impact Categories for overhead curtain wall**

(GWP = Global warming potential (IPCC); AP = Acidification potential; EP = Eutrophication potential; ODP = Stratospheric ozone layer depletion potential; FF = Resources, Fossil fuels; SFP = Smog formation potential)



**Figure 4. Overhead curtain wall resource use indicators (zero values are not shown in the graph)**

(RPRE = Renewable primary resources used as energy carrier; NRPRE = Non-renewable primary resources used as an energy carrier; NRPRM = Non-renewable primary resources with energy content used as material; SM = Secondary material; FM = Use of net freshwater resources)



# ENVIRONMENTAL PRODUCT DECLARATION



Overhead Glazing  
Aluminum Sloped Curtain Wall

According to ISO 14025, EN 15804, and ISO 21930:2017




Figure 5. Overhead curtain wall output and waste flows (zero values are not shown in the graph)

(HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; HLRW = High-level radioactive waste; ILLRW = Intermediate- and low-level radioactive waste; MFR = Materials for Recycling)

## Additional Information

### Disclosure of Windows Hazardous Content

There are no materials present in at least 0.1% of the overhead glazing that are known to be hazardous to human health and the environment nor on the Candidate List Substances of Very High Concern (EPA, 2021).

### Recyclable Content

Aluminum is a highly efficient sustainable building material. Aluminum is 100% recycleable and can be recycled repeatedly. The performance of recycled aluminum is identical to the one of smelted aluminum but requires only 1/20 of the energy to manufacture. In building and construction aluminum scrap has a recycling rate of 95% (EAA, 2021; UNEP, 2011). The remaining 5% is sent to landfill.

## Bibliography

Bare, J. (2012). Tool for the Reduction and Assessment of Chemical and other Environmental Impacts (TRACI) - Software Name and Version Number: TRACI version 2.1 - User's Manual. Washington, D.C.: U.S. EPA.



# ENVIRONMENTAL PRODUCT DECLARATION



**Overhead Glazing**  
Aluminum Sloped Curtain Wall

According to ISO 14025, EN 15804, and ISO 21930:2017

- EAA. (2021). <https://www.european-aluminium.eu/>. Retrieved from European Aluminum Website.
- EPA. (2021). Retrieved from <https://www.epa.gov/environmental-topics/chemicals-and-toxics-topics>
- GaBi. (2021). Retrieved from <https://gabi.sphera.com/support/gabi/gabi-lcia-documentation/cml-2001/>
- GHG protocol. (2014). 20 Greenhouse Gas Protocol, Emissions factors from cross-sector tools; <http://www.ghgprotocol.org/calculation-tools/all-tools>.
- IAP-USA. (2021). Retrieved from Industrial painting USA: <https://industrialpaintingusa.com/project/painting-aluminum-mills/>
- IBU. (2019). Part B: Requirements on the EPD for Self supporting façade elements based on glazed curtain walls (IBU, V1.7, 04.01.2019) .
- IBU/UL. (2014). PCR Guidance-Texts for Building-Related Products and Services: Part B: Requirements on the EPD for Products of aluminium and aluminium alloys. Berlin. IBU/UL.
- IBU/UL. (2014). Product Category Rules for Building-Related Products and Services: Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project report. Königswinter. IBU/UL.
- IBU/UL. (2018). Part A: Calculation Rules for the LCA and Requirements Project Report.
- Kawneer. (2021). Retrieved from [https://www.kawneer.com/kawneer/north\\_america/catalog/97911/ADMD070EN.pdf](https://www.kawneer.com/kawneer/north_america/catalog/97911/ADMD070EN.pdf)
- Sphera. (2020). GaBi energy database, retrieved from Sphera Solutions Inc, <http://www.gabi-software.com/support/gabi/gabi-database-2019-lci-documentation/extension-database-ii-energy/>.
- Sphera. (2020). GaBi LCA Database Documentation. Retrieved from Sphera Solutions, Inc.: <http://www.gabi-software.com/america/support/gabi/>.
- UL Environment. (2015). PCR Guidance for Building-Related, Part B: Non-Metal Ceiling Panel EPD Requirements.
- UL Environment. (2018). PCR Guidance for Building-Related Products and Services - Part B: Building Envelope Thermal Insulation EPD Requirements.
- UNEP. (2011). Recycling Rates of Metals : A Status Report. Retrieved from UNE Document Repository: [https://wedocs.unep.org/bitstream/handle/20.500.11822/8702/Recycling\\_Metals.pdf?sequence=1&isAllowed=y](https://wedocs.unep.org/bitstream/handle/20.500.11822/8702/Recycling_Metals.pdf?sequence=1&isAllowed=y)
- Worldsteel. (2017). Retrieved from [https://www.worldsteel.org/en/dam/jcr:6eefabf4-f562-4868-b919-f232280fd8b9/LCI%2520methodology%2520report\\_2017.pdf](https://www.worldsteel.org/en/dam/jcr:6eefabf4-f562-4868-b919-f232280fd8b9/LCI%2520methodology%2520report_2017.pdf)

