


PRODUCT GREEN GUIDE

1600 Wall System™3 & 4 Curtain Wall

The 1600 Wall System™3 and 1600 Wall System™4 curtain walls offer inside glazing, ease of fabrication, low installation costs, design options, and high thermal and structural performance.



RATING SYSTEMS

LEED v4 BD+C: New Construction

- EA: Optimize Energy Performance
- EA: Renewable Energy Production
- MR: Environmental Product Declarations
- MR: Sourcing of Raw Materials
- MR: Material Ingredients
- MR: Source Reduction - Lead, Cadmium, and Copper
- MR: Construction and Demolition Waste Management
- EQ: Thermal Comfort
- EQ: Daylight
- EQ: Quality Views
- EQ: Acoustic Performance

Living Building Challenge 3.1

- | | |
|---|---|
| <input checked="" type="checkbox"/> IMP 06: Net Positive Energy | <input type="checkbox"/> IMP 12: Responsible Industry |
| <input type="checkbox"/> IMP 07: Civilized Environment | <input checked="" type="checkbox"/> IMP 13: Living Economy Sourcing |
| <input checked="" type="checkbox"/> IMP 08: Healthy Interior | <input checked="" type="checkbox"/> IMP 14: Net Positive Waste |
| <input checked="" type="checkbox"/> IMP 09: Biophilic Environment | <input type="checkbox"/> IMP 16: Universal Access |
| <input checked="" type="checkbox"/> IMP 10: Red List | |

WELL Building Standard

- | | |
|---|---|
| <input checked="" type="checkbox"/> 01: Air Quality Standards | <input checked="" type="checkbox"/> 28: Cleanable Environment |
| <input type="checkbox"/> 03: Ventilation Effectiveness | <input checked="" type="checkbox"/> 54: Circadian Lighting |
| <input checked="" type="checkbox"/> 04: VOC Reduction | <input type="checkbox"/> 56: Solar Glare Control |
| <input type="checkbox"/> 08: Healthy Entrance | <input checked="" type="checkbox"/> 61: Right to Light |
| <input checked="" type="checkbox"/> 11: Fundamental Material Safety | <input checked="" type="checkbox"/> 62: Daylight Modeling |
| <input checked="" type="checkbox"/> 12: Moisture Mgmt | <input checked="" type="checkbox"/> 63: Daylight Fenestration |
| <input checked="" type="checkbox"/> 14: Air Filtration Mgmt | <input type="checkbox"/> 72: Accessible Design |
| <input type="checkbox"/> 15: Increased Ventilation | <input checked="" type="checkbox"/> 74: Exterior Noise Intrusion |
| <input type="checkbox"/> 19: Operable Windows | <input type="checkbox"/> 76: Thermal Comfort |
| <input checked="" type="checkbox"/> 25: Toxic Material Reduction | <input checked="" type="checkbox"/> 97: Material Transparency |
| <input type="checkbox"/> 26: Enhanced Material Safety | <input checked="" type="checkbox"/> 98: Organizational Transparency |

FEATURES

- 2-1/4" (57.2mm) to 2-1/2" (63.5mm) sightlines
- 6" (152.4mm) or 7-1/2" (190.5mm) standard depths
- High thermal performance
- Low to high rise application
- Inside or outside glazing options
- IsoStrut™ Thermal Break for structural & thermal performance
- 1600 Wall System™3 allows structural silicone glazing (SSG)
- 1600 Wall System™4 has easy and fast shear block fabrication
- Two color option
- Standard anodized finishes only

DOCUMENTS



Environmental Product Declaration

Document no. 47868332121.105.1
Product-specific Type III EPD



Material Transparency Summary

Document no. MTSD030EN
Manufacturer Material Ingredient Inventory